

MAGPRO 75/4S

The robust allrounder with 4 speeds:
twist drilling, core drilling & tapping




Scope of delivery:

Safety chain, coolant tank, tool, chip protection, ejector wedge, case, CM3 / Weldon 19

Optional:

Pipefix - pipe clamping system
Clamping range from 32 to 600 mm
Ref. 490010big



Delivery in a carry case



Optional: drill chuck 16 mm and adapter Art. 490164

Thread cutting



Technical specifications	
Power input	1.800 W
Voltage	230 V / 50 Hz
No load / full load speeds	1: 210 / 120 min ⁻¹ 2: 270 / 160 min ⁻¹ 3: 410 / 290 min ⁻¹ 4: 530 / 310 min ⁻¹
Shank	19/32 mm Weldon, MT3
Max. Ø core drills x L	12 - 75 x 75 mm
Max. Ø twist drills x L	16 x 110 mm
Max. Ø twist drills x L MT3	32 x 150 mm
Max. Ø countersinks	55 mm
Max. drilling depth x Ø	75 x 75
Tapping	M4-M22
Stroke	100 mm
Magnetic adhesion	32.000 N
Magnetic surface	200 x 100 mm
Cooling system	integrated, automatic
Net weight	24,8 kg

Description	Reference
Delivery 75/4s - 230V in carry case with safety chain, tools and CM3 / 19 mm adapter (490167)	490160
Accessories (optional)	Reference
HSS-Co core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin	490145
Carbide tipped core drill set 30 mm Ø 1x12, 1x 14, 1x16, 1x18, 1x20, 1x22 mm + pilot pin	490148
„Goldfinger“ core drill set TiN-coated 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin	490145TiN
MT3 quick change adapter set for thread cutter shank	490162
Quick change insert M3-M14 (single)	490162 M3-14
MT3 quick change adapter set for thread cutter shank M5-M22	490165
Quick change insert M5-M22 (single)	490165 M5-22
MT3 / 19 mm adapter	490167
Weldon 32/MT3 adapter for magnetic drills from Ø 61 mm	490163
Drill chuck and adapter 16 mm	490164
Pipefix pipe clamping system for pipes Ø 32 - 127 mm	490010
Pipefix pipe clamping system for pipes Ø 32 - 600 mm	490010BIG
High-performance drilling and cutting oil spray (400 ml)	490020
Magnetic chip collector	490153
HSS-countersinks with Weldon 19 shank on page 61	