



HAND DRY CUTTER 8230N

THE AGILE

- Ideal for cutting sheet metal, sandwich panels, pipes and steel profiles, non-ferrous materials and composites
- By default fitted with a Ø 230 mm/48T resharpenable saw blade for highest cutting lives and a high cutting quality
- Optionally with an impact-resistant LBS saw blade especially designed for gratings
- Strong and light construction, only 7,1 kg
- Chip collector for clean work
- No need for lubrication
- Maximum cutting depth 82/56 mm bevel cut and thickness 10 mm
- Set of 2 adapters for guide rail



CHIP COLLECTOR



Ideal for cutting metal grids with LBS saw blade impact-resistant
Ref. 608280LBS



Optional: Guide rail 1.400 mm with 2 C-clamps 608275SET



Depth adjustment with scaling



Chip collector



45° bevel cut

Power input	Voltage	No load speed	Net weight	Blade size	Bore	Cable length
1.700 W	230V / 60Hz or 115V / 60Hz	2.200 min ⁻¹	7,1 kg	Ø 230 mm	Ø 25,4	5 m

Hand Dry Cutter 8230N + carry case	Reference
with Ø 230 / 48T Inox saw blade 230V	608280I
with Ø 230 / 48T Inox saw blade 115V	608280iUS
with Ø 230 / 48T Inox saw blade 230V + adjustable guide rail integrated clamping system only 90° cut	608280ICG
with Ø 230 / 60T LBS saw blade impact-resistant 230V	608280LBS
with Ø 230 / 48T Inox saw blade 230V and guide rail set 1.400 mm incl. 2 quick release clamps and a set of 2 adapters for guide rail 1.400 mm	608280ISET

Max. cutting capacities	90°		45° (bevel cut)	
	Round	Square	Angle	Plane
	82 x 6 mm	82 x 82 x 6 mm	82 x 82 x 6 mm	10 mm
	56 x 4 mm	56 x 56 x 4 mm	56 x 56 x 4 mm	8 mm
Cutting depth	82 mm	56 mm		

Saw blades	Reference
Ø 230/48T	72123048
Ø 230/48T steel and stainless steel	72123048I
Ø 230/48T steel and stainless steel - coated food and construction	72123048NSF
Ø 230/60T - aluminum	72123060
Ø 230/68T - thin walled material	72123068
Ø 230/84T - thin sheets	72123084
Ø 230/60T - LBS metal grids	72223060

Accessories	Reference
Cutting guide rail with integrated clamping system (600 - 1200 mm)	608284
Guide rail set 1.400 mm incl. 2 quick release clamps and 2 adapters	608275ASET
Set of 2 adapters for Guide rail 1.400 mm	608275A
Connector for guide rail	608275B