

WRAPAROUND TUBE SANDER POLISHER 760/40



- Applicable for rough grinding up to mirror polishing
- High efficiency motor with variable fullwave feedback
- Electronic speed control with soft start
- High stable pulleys allow precise control of abrasive belts
- Tool-free change of abrasives
- The large wraparound angle allows easy and fast preparing and finishing of tube constructions (e.g. railings)



Perfect for the finishing of pipe constructions



Fits perfectly with up to 270° contact for all curves



Starter Pack
Ref. 495050

Accessories included

- 1: Carry case (572 x 362 x 238 mm)
- 2: Sandpaper belts
80 (40 x 760 mm) 1 piece each
100 (40 x 760 mm) 1 piece each
120 (20 x 760 mm) 1 piece each
- 3: Surface conditioning belt (40 x 760 mm)

Technical Specifications

Power input	1.200 W
Voltage	230 V / 50 Hz
No load speed	1.600 - 3.200 min ⁻¹
Surface speed	3 - 12 m/s
Max. belt length	760 mm
Max. belt width	40 mm
Net weight	3,4 kg

Description	Reference
Delivery in hard carry case with accessories	495050

ACCESSORIES FOR WRAPAROUND TUBE SANDER / POLISHER 760/40

HIGH PERFORMANCE ZIRCON ABRASIVE BELTS

Description

- Cotton/polyester backing with additive, aluminium oxide grain, double resin, close coat.

Main features and benefits

- Extremely long life and highly efficient removal. Coarser grits are suitable for heavy scrubbing of steel and cast iron. It is also suitable for wet applications.

Recommended applications

- grinding and cleaning, deburring, removing small protruding welded surfaces or welding spots.

Work surfaces

- Standard steel, stainless steel, non ferrous metals, cast iron, alloys.



Description as above	Packaging	Reference
Abrasive belts 40 x 760 mm - P080	10 pcs	495WS080
Abrasive belts 40 x 760 mm - P100	10 pcs	495WS100
Abrasive belts 40 x 760 mm - P120	10 pcs	495WS120

SURFACE CONDITIONING BELTS X-FLEX

This material is unique in the market. Its particular structure makes it very flexible and it prevents delamination. Ideal to work in narrow belts form and it is easy to fit on very compact machinery.

Description as above	Packaging	Reference
X-Flex - Brown 40 x 760 mm - coarse	20 pcs	495WS103
X-Flex - Red 40 x 760 mm - medium	20 pcs	495WS104
X-Flex - Blue 40 x 760 mm - very fine	20 pcs	495WS105

