


MAGPRO 150 M42

Core drilling up to Ø 150 mm
Thread cutting up to M42
Twist drilling up to Ø 46 mm


- Heavy duty reversible motor unit
- 4 Gears, 8 Speeds
- MT4 arbor
- Patented guide: for large machines subjected to constant intensive load, the classic dovetail guide can be dispensed with
- Highest stability without extra support
- Overload protection

Scope of delivery:

case, MT4/Weldon 19 & 32 adapter, safety chain, carabina and hexagon key



Patented guide



Technical specifications

Power input	2.400 W
Voltage	230 V / 50 Hz
No load speeds	80/60 min ⁻¹ 165/125 min ⁻¹ 275/205 min ⁻¹ 545/410 min ⁻¹
Shank	19/32 mm Weldon, MT4
Max. tapping capacity	M5 - M42
Max. Ø core drills	150 mm
Max. Ø twist drills (MT4)	46 mm
Magnetic adhesion	20.500 N
Dimensions [mm]	630 (930) x 210 x 390
Stroke	300 mm
Net weight	42 kg

Description	Reference
Magpro 150 M42 - in case with MT4 Weldon 32 adapter, safety chain, carabina and hexagon key	491150N
Accessories (optional)	Reference
HSS-Co core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin	490145
Carbide tipped core drill set 30 mm Ø 1x12, 1x14, 1x16, 1x18, 1x20, 1x22 mm + pilot pin	490148
Gold finger core drill set TiN-coated 30 mm Ø 12, 14, 16, 18, 20, 22 + pilot pin	490145TiN
HSS-Co core drill set Ø 9/16", 5/8", 11/16", 3/4", 13/16", 15/16" x 1 + pilot pin	490145IN
MT4 / Weldon 19 mm adapter (included)	490167MK4
MT4 / Weldon 32 mm adapter (included)	490163MK4
MT4 quick change adapter for thread cutter M5-M22	491151
Quick change insert M5-M22 (single)	490165 M5-22
MT4 quick change adapter for thread cutter M14-M30	491152
Quick change insert M14-M30 (single)	490169 M14-30
MT4 quick change adapter for thread cutter M20-M42	491153
Quick change insert M20-M42 (single)	491153 M20-42
High-performance drilling and cutting oil spray (400 ml)	490020
Magnetic chip collector	490153