

MAGPRO 35 STANDARD



Technical specifications

Power input	1.100 W
Voltage	230 V / 50 Hz
No load / full load speed	620 / 350 min ⁻¹
Shank	19 mm Weldon
Max. Ø core drills x L	12 - 35 x 50 mm
Max. Ø twist drills x L	13 x 110 mm
Max. Ø countersink	30 mm
Stroke	80 mm
Magnetic adhesion	15.000 N
Magnetic surface	165 x 80 mm
Cooling system	integrated, automatic
Net weight	12 kg

Description	Reference
Magpro 35 - delivery in carry case with safety chain and maintenance tools	490150

Accessories (optional)	Reference
HSS-Co core drill set 30 mm Ø 12, 14, 16, 18, 20, 22 mm with pilot pin	490145
Carbide tipped core drill 30 mm Ø 1x12, 1x 14, 1x16, 1x18, 1x20, 1x22 mm with pilot pin	490148
Gold finger core drill TiN-coated 30 mm Ø 12,14,16,18, 20, 22 + pilot pin	490145TiN
HSS-Co core drill set Ø 9/16", 5/8", 11/16", 3/4", 13/16", 15/16" x 1 + pilot pin	490145IN
Drill chuck and adapter 13 mm	490152
Quick release for Magpro 35	490151
Magnetic chip collector	490153
High performance cutting oil spray for optimal cooling and higher cutting performance (400 ml)	490020
HSS-countersinks with Weldon 19 shank on page 69	



Compact and sturdy

- Twist drilling up to Ø 13 mm
- Core drilling from Ø 12 - 35 mm
- Shank Weldon 19 mm

Scope of delivery:

Tension belt, coolant tank, tool, chip protection, carry case



Twist drilling up to 13 mm



Optional: 13 mm drill chuck & adapter Ref. 490152



Optional: quick release Ref. 490151



Optional: Magnetic chip collector Ref. 490153



Optional: 3 different sets Core drill set with pilot pin



HSS-Countersink 30 mm with Weldon 19 mm shank Ref. 490153