



HAND DRY CUTTER 8230 AIR

AIR OPERATED



Metal cutting circular saw by Jepson Power for fast and low-burr cutting of metal pipes and profiles without cooling

- Ideal for cutting sheet metal, sandwich panels, metal plates, tubes and profiles made of steel, non-ferrous materials and composites
- Solid and light, only 8.6 kg
- Chip collecting container for clean work
- Lubricant unnecessary
- Maximum cutting depth of 82 mm / 56 mm bevel cut up to a thickness of 10 mm
- Set of 2 adapters for guide rail

Scope of delivery:


Carry case + Ø 230 / 48T CT saw blade for steel and stainless steel
OR Carry case + Ø 230 / 60T CT saw blade „LBS impact resistant“
for thin-walled steel, grids and gratings



CHIP COLLECTOR



Ideal for cutting metal grids with LBS saw blade
Art.: 608100LBS



Optional: Guide rail 1.400 mm with 2 C-clamps 608275SET



Cutting depth of 82 mm



Depth adjustment with scaling



Chip collector

Technical specifications	
Operating pressure (flow pressure)	6 bar
Bore	Ø 25,4
Motor output	1.500
No speed load	1.700 min ⁻¹
Air consumption	circa 2 m ³ / min
Air connection	R ½"
ID of hose	mind. Ø 13 mm
Net weight	8,6 kg
Blade size	230 mm
Noise level (1 m distance)	103,3 dB (A)
Vibration level no load speed	< 2,5 m/s ²

Max. cutting capacities	90°		45° (bevel cut)	
	Round	Square	Round	Square
Round	82 x 6	56 x 4	56 x 4	56 x 4
Square	82 x 82 x 6	56 x 56 x 4	56 x 56 x 4	56 x 56 x 4
Angle	82 x 6	56 x 4	56 x 4	56 x 4
Plan	10	8	8	8
Cutting depth	82	56	56	56

Hand Dry Cutter 8230 AIR	Reference
with Ø 230/48T standard saw blade + carry case	608100
with Ø 230/60T LBS saw blade + carry case	608100LBS
Saw blades	Reference
230 / 48T standard for steel	72123048
230 / 48T for stainless steel / steel	72123048I
230 / 48T for stainless steel food & construction coated	72123048NSF
230 / 60T for aluminum	72123060
230 / 68T for thin-walled material	72123068
230 / 84T for thin sheet metal	72123084
230 / 60T LBS impact-resistant	72223060

Accessories	Reference
Cutting guide rail with integrated clamping system (600 - 1200 mm)	608284
Guide rail set 1.400 mm incl. 2 quick release clamps	608275SET
Set of 2 adapters for Guide rail 1.400 mm	608275A
Connector for guide rail	608275B