



# HAND DRY CUTTER 8230N

## THE AGILE

- Ideal for cutting sheet metal, sandwich panels, pipes and steel profiles, non-ferrous materials and composites
- Strong and light construction, only 7,1 kg
- Chip collector for clean work
- No need for lubrication
- Maximum cutting depth 82/56 mm bevel cut and thickness 10 mm
- Set of 2 adapters for guide rail

**Scope of delivery:**  
 Ø 230 / 48T CT saw blade for steel and stainless steel  
 OR  
 Ø 230 / 60T CT saw blade „LBS impact resistant“  
 for thin-walled steel, grids and gratings



CHIP COLLECTOR




Ideal for cutting metal grids with LBS saw blade impact-resistant  
 Ref. 608280LBS



Optional: Guide rail 1.400 mm with 2 C-clamps 608275SET



Depth adjustment with scaling



Chip collector



45° bevel cut

Power input	Voltage	No load speed	Net weight	Blade size	Bore	Cable length
1.700 W	230V / 50Hz or 115V / 60Hz	2.200 min <sup>-1</sup>	7,1 kg	Ø 230 mm	Ø 25,4	5 m

Hand Dry Cutter 8230N + carry case	Reference
with Ø 230 / 48T Inox saw blade (230V)	608280I
with Ø 230 / 48T Inox saw blade (115V)	608280IUS
with Ø 230 / 48T Inox saw blade (230V) + adjustable guide rail integrated clamping system (90° cut only)	608280ICG
with Ø 230 / 60T LBS saw blade impact-resistant (230V)	608280LBS
with Ø 230 / 48T Inox saw blade (230V) + guide rail set 1.400 mm incl. 2 quick release clamps + 2 adapters	608280ISET

	Max. cutting capacities	
	90°	45° (bevel cut)
<b>Round</b>	82 x 6 mm	56 x 4 mm
<b>Square</b>	82 x 82 x 6 mm	56 x 56 x 4 mm
<b>Angle</b>	82 x 82 x 6 mm	56 x 56 x 4 mm
<b>Plane</b>	10 mm	8 mm
<b>Cutting depth</b>	82 mm	56 mm

**ECO-FRIENDLY**  
with Dry Cutting-Technology



### ACCESSORIES (OPTIONAL)

Selecting the correct number of teeth depends on the wall/diameter of the material. We will be happy to advise you. +49 (0) 2403 64 55 0

Carbide tipped saw blades	Ø [mm]	Teeth	Bore [mm]	Kerf [mm]	Max. Speed	Reference
Steel	230	48	25,4	2,0	3.000 min <sup>-1</sup>	72123048 
Stainless steel & steel	230	48	25,4	2,0	3.000 min <sup>-1</sup>	72123048I 
Stainless steel NSF coated	230	48	25,4	2,0	3.000 min <sup>-1</sup>	72123048NSF 
Aluminum	230	60	25,4	2,0	3.000 min <sup>-1</sup>	72123060 
Steel (thin-walled)	230	68	25,4	2,0	3.000 min <sup>-1</sup>	72123068 
Steel (extra thin-wall)	230	84	25,4	2,0	3.000 min <sup>-1</sup>	72123084 
Steel (thin-walled) "LBS - impact resistant"	230	60	25,4	1,4	3.000 min <sup>-1</sup>	72223060 




**Cutting guide rail with integrated clamping system**  
 Length [mm] 600 - 1200  
 Ref. 608284



**Guide rail SET**  
 Length 1.400 mm  
 Incl. 2 quick release clamps  
 Incl. 2 adapters (608275A)  
 Ref. 608275ASET



**Set of 2 adapters for guide rail 1.400 mm**  
 Ref. 608275A



**Connector for guide rail**  
 Ref. 608275B



**Quick release clamp for guide rail (2 pcs.)**  
 Ref. 608275S